

		TM1	TM2	TM3	TM4
<b>Dimensions Casing:</b>	<b>Length:</b>	28.2in	31.2in	32.7in	46.5in
	<b>Width:</b>	11.9in	23.9in	32.7in	32.7in
	<b>Height:</b>	16.2in	23.5in	32.5in	32.5in
<b>Dimensions Filter Drum:</b>	<b>Diameter:</b>	9.4in	15.8in	25.6in	25.6in
	<b>Length:</b>	13.4in	11.8in	13.8in	27.6in
<b>Dimensions Connections:</b>	<b>Inlet:</b>	1 x 3 in	1 x 4 in	1 x 6 in	1 x 8 in
	<b>Outlet:</b>	1 x 3 in	1 x 4 in	1 x 6 in	1 x 8 in
	<b>Waste Outlet:</b>	1 x 3 in	1 x 4 in	1 x 4 in	1 x 4 in
<b>Total surface area filter screen:</b>		2.7 ft <sup>2</sup>	4.1 ft <sup>2</sup>	7.7 ft <sup>2</sup>	15.4 ft <sup>2</sup>
<b>Effective surface area filter screen:</b>		1.2 ft <sup>2</sup>	1.9 ft <sup>2</sup>	3.7 ft <sup>2</sup>	7.1 ft <sup>2</sup>
<b>Standard mesh size filter screen:</b>		60µm	60µm	60µm	60µm
<b>Standard Flow Rate:</b>		22 - 33 gpm	66 - 88 gpm	132 - 176 gpm	264 - 330 gpm
<b>Motor:</b>		AC 0.18kW	AC 0.18kW	AC 0.18kW	AC 0.37kW
<b>Electrical Supply Sensor/Motor:</b>		24V / 230V / 60Hz			
<b>Classification Control box Casings:</b>		IP66			
<b>Classification Buttons/Switches CB:</b>		IP65			
<b>Electrical Supply Control box:</b>		230V / 60 Hz			
<b><u>Materials of Construction:</u></b>					
<b>HDPE:</b>	Casing, Filter Drum, Support Screen, Waste Water Tray etc.				
<b>Stainless Steel 316:</b>	Drive axis, Screws				
<b>POM:</b>	Drum gear, drive gear				
<b>PP:</b>	Spray Nozzles				
<b>Nylon:</b>	Mesh				

